



SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION.

D-A Lubricant

1340 W. 29th St.
Indianapolis, IN 46208
317/923-5321

CHEMICAL EMERGENCY HOTLINE 800 899-9004

PRODUCT NAME: **KLINGFAST SPECIAL LIGHT**

PRODUCT DESCRIPTION: OPEN GEAR LUBRICANT

CHEMICAL FAMILY: LUBRICANT

EFFECTIVE DATE: 02/19/08

SUPERCEDES DATE: 03/02/05

Dear Customer:

In compliance with the Superfund Amendments and Reauthorization Act (SARA Title III, Section 313), Federal Hazard Communications Regulations (WHMIS and OSHA 29 CFR 1910.1200) and in the interest of informed use of our product, we are providing you with this Material Safety Data Sheet (MSDS).

This MSDS will be updated regularly to reflect the most recent information in our possession. Please ensure that obsolete MSDS sheets in your files for this part number are discarded.

We THANK YOU for your continued patronage and look forward to providing you with additional quality products and services.

SECTION 2 - HAZARDOUS INGREDIENTS

COMPONENT	CAS #	% WT	PEL	TLV	STEL	UNITS	LC50,PPM	LD50,MG/KG
PETROLEUM OILS								
	69029-75-0	10-30	5	5	10	MG/M3		RATI 13000 RABA 2000
PETROLEUM ASPHALT								
	08052-42-4	60-99		5		MG/M3		
MINERAL SPIRITS								
	64742-88-7	5-10	N/A	N/A			RAT>3000	RATI 28000 RABA 4000

SECTION 3 - PHYSICAL DATA

Boiling Pt Deg F/C: 300/149 (Mineral spirit) Specific Gravity: 0.96
 Vapor Pressure (MM HG): 10 % Volatile Volume: 5-10
 Vapor Density (Air=1): 3.9 Evaporation Rate: (Ether=1) <1
 Solubility in Water: NEGLIGIBLE Water/Oil Dist Coeff: 0
 Appearance and Odor: Black oily liquid with mild petroleum odor
 Physical State: LIQUID PH: N/A
 Freeze Pt Deg F/C: >0/-18 Threshold Odor, PPM: N/A
 Other: N/A VOC: Lbs/Gal = N/A
 Grams/Liter = N/A Grams VOC/Gram Solid = N/A
 % VOC: N/A

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

Classification: Combustible NFPA Rating: 0.2.0
 Combustion products: CO, CO2, Smoke
 Flash Point Deg F/C: 104/40 LEL %: 0.8 UEL %: N/A
 Extinguishing Media: Water Fog, Foam, Dry Chemical, CO2, Sand, or Earth.
 UN/NA/PIN#: 1993

Special Fire Fighting Procedures

Firefighters should wear self-contained breathing equipment. Treat as a Class B fire. Use water to cool threatened containers.

Auto Ign. Temp Deg F/C: 473/245

PRODUCT NAME: **KLINGFAST SPECIAL LIGHT**
 EFFECTIVE DATE: 02/19/08 SUPERCEDES DATE: 03/02/05

Unusual fire and explosion hazards: N/A

Explosion Power: Low Impact Sensitive: No

Burning Rate: Low Static Sensitive: No

SECTION 5 - HEALTH HAZARD DATA

Product Guide: TLV see Section 2 STEL: see Section 2

Routes of Entry: Skin contact, Eye, Inhalation, Ingestion

Effects of Overexposure:

Acute; may cause respiratory system, skin, and/or eye irritation.

Ingestion may cause nausea, cramps, diarrhea, and other gastrointestinal disorders.

Chronic; excess skin contact may cause dryness.

Excess inhalation may cause dizziness, giddiness and nausea and may be harmful to respiratory system, central nervous system, blood, liver and kidneys. Excess skin contact and/or ingestion may cause damage to lungs, kidneys, stomach and/or reproductive system.

Any suspected carcinogen = or >0.1%: NO

Emergency and First Aid Procedures

Eye: Immediately flush with water for 15 minutes and call a physician.

Inhalation: If affected, remove to fresh air, administer oxygen and call a physician.

Skin: Wash thoroughly with plenty of water and soap.

Ingestion: Seek a physician immediately, show MSDS or Label; DO NOT induce vomiting.

Wash soiled clothing before wearing again.

SECTION 6 - REACTIVITY DATA

Stable: YES Conditions to Avoid: Heat and flame

Incompatibility (Materials to avoid): YES, strong oxidizing agents

Hazardous Decomposition Products: YES, combustion products, see Section 4

Hazardous Polymerization: NO Conditions to Avoid: N/A

SECTION 7 - SPILL OR LEAK PROCEDURES

Listed in SARA Title III, #302: NO #304, Cercla: YES #313: YES

Steps to be taken in case material is released or spilled:

Eliminate source if safe to do so. Ventilate area. Prevent from entering waterways and drains. Wear suitable personal protective equipment. Dike and absorb with inert material and transfer to a sealed approved container for disposal. Any spill of this material that can enter navigable waters must be reported immediately to the National Response Center (800-424-8802).

Report Quantity, Lb: N/A Kg: N/A TPQ, Lb: N/A

Regulations: SARA, RCRA, PROV/STATE, WHMIS OTHER: N/A

Hazard Waste: EP TOXIC, TOXIC

NO.: D001, U239

Disposal Method: In accordance with Federal, State, and Local Regulations. Do not empty into drains.

*** SARA Waste Characteristic: Ignitable

*** EPA Hazardous Waste Number: N/A

SECTION 8 - SAFE HANDLING AND PROTECTION INFORMATION

Respiratory Protection: Use only in well ventilated areas.

Ventilation - Local: Recommended Special: Avoid Heat/Flame

Mechanical: Recommended Other: N/A

Protective Gloves: Oil/Solvent resistant Eye Protection: Safety Glasses/Goggles

Other Protective Equipment:

Oil/Solvent resistant clothing and footwear. If ventilation is inadequate, wear approved respiratory equipment.

Estimated LD50, Mg/Kg: YES Dermal, Rabbit >2000; Ingestion, Rat 28000

PRODUCT NAME: **KLINGFAST SPECIAL LIGHT**
EFFECTIVE DATE: 02/19/08 SUPERCEDES DATE: 03/02/05

Estimated LC50, PPM: YES Inhalation, Rat >3000
Sensitization: NO
Irritant: YES Maybe eyes Synergistic Agents: NO

SECTION 9 - SPECIAL PRECAUTIONS

Precautions to be taken in handling and storing:

Use only in well ventilated areas. Avoid prolonged or repeated breathing of fumes, vapor, or mist. Avoid contact with eyes and skin. DO NOT take internally. Wash thoroughly after using. In case of accident or illness, consult a physician immediately; show label and/or MSDS.

Keep out of reach of children.

Always read and follow directions on product label.

Other precautions:

More technical information (MSDS) available upon request. For professional industrial use only. Good personal hygiene is important. Empty containers retain residue which can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other ignition sources; they may explode and cause injury or death.

The information and recommendations provided herein are believed to be accurate as of the date hereof. However, such information and recommendations are provided without warranty of any kind and D-A Lubricant disclaims any and all liability or legal responsibility for use or reliance upon same.
