

AutoTrans G-3™



Product Description

D-A AutoTrans G-3™ is an automatic transmission fluid (ATF) that meets on-highway performance requirements for Dexron® III, Allison Type C-4 and Ford Mercon®. It offers excellent corrosion resistance to all types of metals used in transmissions and hydraulic systems, plus provides superior friction retention and thermal and oxidation stability. D-A AutoTrans G-3 can be used in a broad variety of applications found in on- and off-highway service as well as marine and industrial applications.

Product Features and Benefits

Friction modifiers control lock-up rates of clutch packs *for proper transmission shifting characteristics and efficient power transfer.*

Controls seal deterioration to *limit fluid leakage.*

Specially formulated *for extra wear control and rust protection for longer equipment life.*

Special detergent/dispersant additives *limit formation of sludge and varnish deposits which interfere with proper transmission operation.*

Multigraded *for optimum performance during cold starts and high temperature operations.*

Formulated to be compatible with metallurgy *used in most modern transmissions and high pressure hydraulic systems.*

Provides excellent antiwear protection *for hydraulic pumps and power steering systems.*

AutoTrans G-3™



Service Applications

Transmissions requiring versions of approved Dexron® III, Dexron® II, Dexron®, or Type A fluid, including:

- Allison C-4, C-3 or C-2 (on-highway)
- Domestic and imported passenger cars and light trucks
- GMC
- Mercedes Benz in North America
- Voith
- Volvo

Transmissions requiring Ford Mercon, Type H or Type CJ fluids
Air compressors requiring Dexron III fluid
Sunstrand hydrostatic transmissions and drives requiring Dexron III fluid
Vane and piston hydraulic pumps requiring Dexron III fluid

NOTE: D-A AutoTrans G-3 does NOT meet Dexron VI, Mercon LV, Mercon SP or Mercon V requirements.

Dexron is a trademark of General Motors Inc.
Mercon is a trademark of the Ford Motor Company.

Typical Properties:

Viscosity @

210 °F, SUS	50.8
100 °F, SUS	175.0
100 °C, cSt	7.16
40 °C, cSt	32.7
Viscosity Index	191
Flash Point °F	395
°C	202
Pour Point °F	-40
°C	-40
API Gravity, 60 °F	30.9

**To Order D-A Products, Call 1-800-OIL-LUBE (1-800-645-5823)
Or Fax orders to (317) 923-3884**

D-A Lubricant Company, Inc.
1340 W. 29th Street, Indianapolis, IN 46208 (317) 923-5321 • (317) 923-3884 FAX
www.dalube.com • dalube@dalube.com