

GlyFlo™ Gas Compressor Oil



Product Description

D-A GlyFlo is a unique custom blend of polyalkylene glycols (PAG) with additives for oxidation stability, corrosion protection, metal deactivation and lubricity. The ability of these lubricants to withstand dilution by hydrocarbon and other compressed gas is particularly advantageous in flooded screw compressors. Other advantages include stability, low ash content, high viscosity index, shear stability, and excellent lubricity.

Service Applications

Propane refrigeration compressor lubrication.
Natural gas and other light hydrocarbon compressor applications.

Typical Properties:

<u>GlyFlo Gas Compressor Oil</u>	<u>ISO</u>	<u>220</u>
Viscosity @ 40°C, cSt,	ASTM D445	218.5
Viscosity @ 100°C, cSt		35.9
Viscosity @ 100°F, SUS		1107
Viscosity @ 210°F, SUS		173.3
Viscosity Index,	ASTM D2270	214
Density, lb/gal, 60°F,	ASTM D4052	8.32
Pour Point °F (°C),	ASTM D97	-25 (-32)
Flash Point, C.O.C., °F (°C),	ASTM D92	500 (260)
Fire Point, C.O.C., °F (°C),	ASTM D92	550 (288)
Specific Gravity,	ASTM D4052	0.998

To Order D-A Products, Call 1-800-OIL-LUBE (1-800-645-5823)
Or Fax orders to (317) 923-3884

D-A Lubricant Company, Inc.
1340 W. 29th Street, Indianapolis, IN 46208 (317) 923-5321 • (317) 923-3884 FAX
www.dalube.com • dalube@dalube.com

