

GlyFlo™ Gas Compressor Oil



Product Description

D-A GlyFlo is a unique custom blend of polyalkylene glycols (PAG) with additives for oxidation stability, corrosion protection, metal deactivation and lubricity. The ability of these lubricants to withstand dilution by hydrocarbon and other compressed gas is particularly advantageous in flooded screw compressors. Other advantages include stability, low ash content, high viscosity index, shear stability, and excellent lubricity.

Service Applications

Propane refrigeration compressor lubrication.
Natural gas and other light hydrocarbon compressor applications.

Typical Properties:

<u>GlyFlo Gas Compressor Oil</u>	<u>ISO</u>	<u>100</u>	<u>150</u>	<u>220</u>
Viscosity @ 40°C, cSt,	ASTM D445	92.3	153	218.5
Viscosity @ 100°C, cSt		18.6	23.5	35.9
Viscosity @ 100°F, SUS		464	723	1107
Viscosity @ 210°F, SUS		94.3	115.8	173.3
Viscosity Index,	ASTM D2270	223	196	214
Density, lb/gal, 60°F,	ASTM D4052	8.27	8.29	8.32
Pour Point °F (°C),	ASTM D97	-40 (-40)	-30 (-34)	-25 (-32)
Flash Point, C.O.C., °F (°C),	ASTM D92	500 (260)	500 (260)	500 (260)
Fire Point, C.O.C., °F (°C),	ASTM D92	530 (277)	540 (282)	550 (288)
Specific Gravity,	ASTM D4052	0.992	0.995	0.998

Available by special order only.

Please contact D-A Indianapolis regarding pricing, minimum order quantity and lead time.

To Order D-A Products, Call 1-800-OIL-LUBE (1-800-645-5823)
Or Fax orders to (317) 923-3884

D-A Lubricant Company, Inc.
1340 W. 29th Street, Indianapolis, IN 46208 (317) 923-5321 • (317) 923-3884 FAX
www.dalube.com • dalube@dalube.com

