

Super Speed Sport™

Full Synthetic Motor Oil



Product Description

D-A Super Speed Sport™ fully synthetic motor oil has been designed with the latest high-tech additives and synthetic base oil to exceed the industry's most demanding standards and outperform conventional oils. Exclusive D-A ChemGuard™ additive offers unmatched protection not found in any other motor oil on the market today.

D-A Super Speed Sport has been designed to offer the highest levels of performance, engine cleanliness and protection while meeting requirements of ILSAC GF4 performance standards. The product has been designed to insure quick cold weather engine start up while protecting vital engine parts, and to provide superior protection against wear in high temperature/high stress applications. Super Speed Sport provides superior resistance to viscosity breakdown and foaming in modern engines.

Product Features and Benefits

Full synthetic formulation *helps increase engine life by maintaining oil flow at both high and low temperatures.*

Formulated with exclusive D-A ChemGuard chemistry *which provides outstanding viscosity stability, superior engine cleaning power, deposit control, and wear protection.*

Combination of synthetic base stocks and unique additives *ensures excellent thermal and oxidation stability and outstanding performance during maximum recommended oil drain intervals.*

Excellent low temperature characteristics *permit quick engine starting in cold weather and promptly deliver oil to vital metal parts maximizing engine life.*

Anti-foam agents *permit higher oil pressure for greater protection.*

Super Speed Sport™

Full Synthetic Motor Oil



Service Applications

ACEA A1-02

API Service Categories: SM, SL, SJ, CF
 Chrysler MS-6395N
 Energy Conserving (5W-20, 5W-30, 10W-30)
 Ford WSS-M2C153-F (5W-30, 10W-30)
 Ford WSS-M2C153-G (5W-30, 10W-30)
 Ford WSS-M2C205-A (5W-30)
 Ford WSS-M2C930A (5W-20)
 Ford WSS-M2C929A (5W-30)

GM 6094M
 IGM 4718M (Corvette) (5W-30, 10W-30)
 ILSAC GF4

Gasoline engines.
 Small diesel engines
 (automobiles and pick-up trucks).

Typical Properties:

SAE Grade	5W-20	5W-30	10W-30	10W-40
Viscosity				
@ 100°C, cSt	8.2	10.8	11.1	14.5
@ 40°C, cSt	45.0	58.0	69.3	90.9
Viscosity Index	158	180	152	166
Cold Cranking Viscosity				
@ -30°C, cP	5,300	4,000	--	--
@ -25°C, cP	--	--	5,500	6,100
Cold Pumping Viscosity (SAE Grade Maximum: 60,000 cP)				
@ -35°C, cP	<20,000	<20,000	--	--
@ -30°C, cP	--	--	<30,000	<30,000
Flash Point, °F (°C)	450 (232)	430 (220)	465 (240)	450 (232)
API Gravity	34.1	34.3	33.2	32.9
Lbs/gal	7.12	7.11	7.16	7.17

To Order D-A Products, Call 1-800-OIL-LUBE (1-800-645-5823)
Or Fax orders to (317) 923-3884

D-A Lubricant Company, Inc.
 1340 W. 29th Street, Indianapolis, IN 46208 (317) 923-5321 • (317) 923-3884 FAX
www.dalube.com • dalube@dalube.com