
Product Description

D-A Citrasense™ is a general purpose degreaser designed for use in a broad range of industrial cleaning applications.

This product is formulated with a solvent derived from natural citrus sources. It is designed to be highly efficient for removal of all types of oily and greasy soils including grease, gear oils or corrosion preventatives. Apply Citrasense to soiled surfaces and agitate as necessary to remove stubborn soils. Rinse surface with water to remove soil.

Storage

Store away from heat, sparks and open flame. Store in tightly sealed containers. If storing product in container other than original shipping container, stainless steel tanks or fluorocarbon-barrier plastic containers are recommended.

Product Features and Benefits

Formulated specifically for use in cleaning industrial equipment *including metals, nylon, stainless steel and certain plastics,*
Citrus-based formulation *loosens oils, greases and other soil easily and washes off with water.*

Service Applications

Citrasense is suitable for use in cleaning a wide range of industrial applications.
See **Compatibility Chart** below:

Aluminum	No effect/Excellent	Phenolic	No effect/Excellent
Burma N	No effect/Excellent	Polyethylene	Moderate effect/Fair
Carbon/Ceramic	No effect/Excellent	Polypropylene	Moderate effect/Fair
Carbon/Graphite	No effect/Excellent	PVC	Minor effect/Good
Carpenter 20	No effect/Excellent	Ryton	Unknown
Cast Bronze	No effect/Excellent	Silicone	Severe effect/Not recommended
Ceramagnet A	No effect/Excellent	Stainless steel (304)	No effect/Excellent
Ceramic	No effect/Excellent	Stainless steel (316)	No effect/Excellent
CPV	No effect/Excellent	Stainless steel (440)	No effect/Excellent
Cycolac (ABS)	Minor effect/Good	Teflon	No effect/Excellent
Delrin (Acetal)	Severe effect/Not recommended	Titanium	No effect/Excellent
EPDM	Unknown	Tygon	Moderate effect/Fair
Epoxy	No effect/Excellent	Viton	No effect/Excellent
Hastelloy C	No effect/Excellent		
Hypalon	Unknown		
Kel-F	Unknown		
Kynar (PVDF)	No effect/Excellent		
Natural Rubber	Moderate effect/Fair		
Neoprene	Moderate effect/Fair		
Nitrile	No effect/Excellent		
Noryl	Unknown		
Nylon	No effect/Excellent		

Recommended Gasket Material:

Man-holes use Viton
Pump parts use Teflon
O-Rings use Fluro-Silicon
Rubber gaskets must be periodically replaced.

Typical Properties:

Appearance	Clear Liquid
Odor	Citrus
Density, pounds per gallon	7.1
Flash Point, °F	115
VOC%	94.5

**To Order D-A Products, Call 1-800-OIL-LUBE (1-800-645-5823)
Or Fax orders to (317) 923-3884**

D-A Lubricant Company, Inc.
1340 W. 29th Street, Indianapolis, IN 46208 (317) 923-5321 • (317) 923-3884 FAX
www.dalube.com • dalube@dalube.com