

RedPlex™



Product Description

D-A RedPlex™ is a general purpose lithium grease formulated for excellent mobility and pumping ease in centralized lubrication systems. RedPlex No. 2 grade offers better low temperature grease delivery to critical lubrication points than most No. 1 grades. The red color makes this grease easy to identify during application and operation. The combination of extreme pressure additives and a stable soap structure results in a high quality grease capable of protecting heavily loaded machinery, while remaining in place.

Product Features and Benefits

Special blend of extreme pressure additives *limits wear and reduces friction in normal and severe machine service.*

Rust and corrosion preventatives *protect both ferrous and non-ferrous metals in damp or corrosive environments.*

Red color makes RedPlex™ *easy to identify during application and operation.*

Good shear stability and bleed resistance *protect against grease leakage and help control lubrication costs.*

Pumps easily from tubes and other types of containers, *perfect for use in central lubrication systems or in all weather conditions.*

Service Applications

General Lubrication

Bearings
Track Rollers
Drive Rollers
Fittings

Pivot Pins

5th Wheel Applications
Semi-Trailer Landing Gears
Semi-Trailer Wheel Axle Bearings

Typical Properties:

<u>NLGI Grade</u>	<u>00</u>	<u>0</u>	<u>1</u>	<u>2</u>
Color	Red	Red	Red	Red
Soap Type	Lithium	Lithium	Lithium	Lithium
Penetration @ 77 °F Worked 60 strokes	400-430	355-385	310-340	265-295
Grease Mobility grams/min.				
@ 77 °F	1207	1027	997	767
@ 20 °F	29	24	19	15
@ 0 °F	3.8	2.1	1.8	1.2
Base Oil Viscosity				
@ 40 °C, cSt	----- 180 - 220 cSt -----			
@ 100 °C, cSt	----- 15.5 - 17.5 cSt -----			
Timken OK Load, lbs.	40	40	40	40
Four-Ball Wear, Scar mm	.52	.52	.52	.52
Four-Ball Weld, Kg	315	315	315	315
Rust Protection	Pass	Pass	Pass	Pass

**To Order D-A Products, Call 1-800-OIL-LUBE (1-800-645-5823)
Or Fax orders to (317) 923-3884**

D-A Lubricant Company, Inc.
1340 W. 29th Street, Indianapolis, IN 46208 (317) 923-5321 • (317) 923-3884 FAX
www.dalube.com • dalube@dalube.com