

**WearGuard™ D-A SYN PCO** (Proofer Chain Oil) is a high performance H-2 synthetic ester lubricant designed for conveyor roller ball bearing chains, pin and roller chains, slides and gears operating in environments which contain high humidity such as a proofer box's in bakeries. This lubricant is blended with D-A's advanced **ChemGuard™** additive technology. It outperforms mineral based petroleum oil lubricants by significantly reducing lubricant consumption and providing better film strength that protects against rust, corrosion, and wear.

## Applications

- Conveyor Roller Ball Bearing Chains
- Pin and Roller Chains
- Slides and Gears in High Humidity Environments

## Characteristics

- Provides outstanding metal wear resistance
- Excellent rust protection
- Does not emulsify with significant amounts of water
- Resists Gumming
- H-2

## Typical Properties

WearGuard™ D-A SYN PCO	ASTM Method	WearGuard D-A SYN PCO 100	WearGuard D-A SYN PCO 150
SAE Grade	J-300	30	40
ISO Viscosity Grade	D2422	100	150
Viscosity, cSt, 40° C/100° C	D445	91.4 / 9.3	146.5 / 13.3
Viscosity Index	D2270	71	90
Pour Point, °C / °F	D97	-29/-30	-34/-30
Flash Point, °C / °F	D92	260/500	271/520
Carbon Residue %	D189	<0.02	<0.02
Evaporation %	D972	0.98	0.90
Foaming Sequences I, II, III	D892	Nil	Nil
Copper Corrosion 3hr @ 100° C	D130	1b	1a
Four Ball Wear 40kg, 1200rpm 1hr @ 75° C	D4172	0.38mm	0.38mm
Specific Gravity	D1298	0.95	0.94
USDA Authorization	-	H-2	H-2
Demulsibility @ 130° F	D1401	Excellent	Excellent



801 Edwards Drive - Lebanon, IN 46052  
1-800-OIL-LUBE (1-800-645-5823)  
(317) 923-5321 (765) 482-3065 FAX  
www.dalube.com dalube@dalube.com

DA-PCO new 12/2012 rev 7/13  
The information in this bulletin is, to the best of our knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.  
© 2013, D-A Lubricant Company, Inc.