

WearGuard™ D-A SYN 8000i Series are fully synthetic lubricants formulated with superior polyalkylene glycol (PAG)-based oils. These premium lubricants are designed for use in compressors and vacuum pumps compressing polar gases, such as NH₃, CO₂, and propane. They are blended with D-A's advanced **ChemGuard™** additive technology and offer excellent rust resistance and are excellent in wet gas compression. The **WearGuard™ D-A SYN 8000i Series** yields a compressor service life of 8,000 – 10,000 hours under good operating conditions. This product is also recommended for Rotary Screw, Rotary Vane, Centrifugal, and Reciprocating Compressors including Vacuum Pump operations.

Characteristics

- Resists hydrocarbon washout/dilution
- Extended drain life
- Reduced sludge and deposit formation
- Excellent oxidative and thermal stability

Typical Properties

WearGuard™ D-A SYN 8000i Series	ASTM Test	WearGuard™ D-A SYN 8046i	WearGuard™ D-A SYN 8068i	WearGuard™ D-A SYN 8100i	WearGuard™ D-A SYN 8150i	WearGuard™ D-A SYN 8220i
ISO Viscosity Grade ---		46	68	100	150	220
Viscosity @ 40°C,cSt	ASTM D445	46	69	106	154	220
Viscosity @ 100°C,cSt	ASTM D445	9.4	12.9	18.9	25.7	34.5
Viscosity Index	ASTM D2270	191	193	195	195	205
Flash Point, °C/°F	ASTM D92	210/415	230/445	230/445	230/445	230/445
Pour Point, °C/°F	ASTM D97	-50/-60	-40/-40	-40/-40	-38/-36	-38/-36
FZG Load Stage	DIN-51354	11	11	11	12	n/a
Four ball wear-40Kg.,1200rpm, 1 hr@75°C, Scar Diameter, mm	ASTM D4172	0.53	0.52	0.51	0.51	n/a
Specific Gravity	ASTM D1298	0.98	0.98	0.98	0.99	0.99
Density, lb/gal 60°F	D4052	0.99	0.99	0.99	0.99	0.99

Note: this product was previously available in the D-A product line as GlyFlo.



801 Edwards Drive Lebanon, IN 46052
 1-800-OIL-LUBE (1-800-645-5823)
 (317) 923-5321 (765) 482-3065 FAX
www.dalube.com dalube@dalube.com

DA-SYN8000i rev 7/2013

The information in this bulletin is, to the best of our knowledge, true and accurate, but all recommendations or suggestions are made without guarantee, since the conditions of use are beyond our control.

© 2013, D-A Lubricant Company, Inc.