

## Product Description

D-A AutoTrans G-3<sup>™</sup> is an automatic transmission fluid (ATF) that meets on-highway performance requirements for Dexron<sup>®</sup> III H, Allison Type C-4 and Ford Mercon<sup>®</sup>. It offers excellent corrosion resistance to all types of metals used in transmissions and hydraulic systems, plus provides superior friction retention and thermal and oxidation stability. D-A AutoTrans G-3 can be used in a broad variety of multi-vehicle applications found in on- and off-highway service as well as marine and industrial applications.

## Product Features and Benefits

Friction modifiers control lock-up rates of clutch packs for proper transmission shifting characteristics and efficient power transfer.

Controls seal deterioration to limit fluid leakage.

Specially formulated for extra wear control and rust protection for longer equipment life.

Special detergent/dispersant additives limit formation of sludge and varnish deposits which interfere with proper transmission operation.

Multigrade for optimum performance during cold starts and high temperature operations.

Formulated to be compatible with metallurgy used in most modern transmissions and high pressure hydraulic systems.

Provides excellent antiwear protection for hydraulic pumps and power steering systems.

## Typical Applications

Transmissions requiring:

Dexron<sup>®</sup> III H

Dexron<sup>®</sup> III G

Dexron<sup>®</sup> II D

Allison C-4

Allison TES-389B

Domestic and imported passenger cars and light trucks

GMC

Ford Mercon<sup>®</sup>

Type A Suffix A (TASA)

Mercedes Benz in North America

Voith

Volvo 37325

NOTE: D-A AutoTrans G-3 does NOT meet Dexron VI, Mercon LV, Mercon SP or Mercon V requirements.

Dexron is a trademark of General Motors Inc.

Mercon is a trademark of the Ford Motor Company.

NOTE: ATF recommendations may vary between models from a manufacturer. Please consult the owners manual for the correct fluid recommendations.



**D-A Lubricant Company, Inc.**

801 Edwards Drive, Lebanon, IN 46052 • TEL: 317.923.5321 • FAX: 765.482.3065 • EMAIL: dalube@dalube.com  
www.dalube.com



## Typical Properties

<b>D-A AutoTrans G-3 Typical Properties</b>		
Test	Method	
Viscosity @210 °F, SUS	ASTM D445	50.8
Viscosity @100 °F, SUS	ASTM D445	175
Viscosity @100 °C, cSt	ASTM D445	7.16
Viscosity @40 °C, cSt	ASTM D445	32.7
Viscosity Index	ASTM D2270	191
Flash Point °F	ASTM D92	395
°C	ASTM D92	202
Pour Point °F	ASTM D96	-40
°C	ASTM D96	-40
API Gravity, 60 °F	ASTM D287	33.8
D-A Product Part Number:		
Bulk		54501
Tote, 220 Gal		54503
Drum, 55 Gal		54502
Pail, 5 Gal		54508 (plastic)
Pail, 5 Gal		54509 (metal)
Quart Case, Net 3 Gal		54506

To Order D-A Products, Call 1-800-OIL-LUBE (1-800-645-5823) or Fax orders to 765-482-3065

**D-A Lubricant Company, Inc.**

801 Edwards Drive, Lebanon, IN 46052 • TEL: 317.923.5321 • FAX: 765.482.3065

Email: [dalube@dalube.com](mailto:dalube@dalube.com) • [www.dalube.com](http://www.dalube.com)

