

Product Description

All Season D-A BAR AND CHAIN OIL is formulated to insure good performance on all link chain and chain bars including chain saw bars. Premium quality D-A BAR AND CHAIN OIL extends the life of the bar, chain and sprocket by protecting against wear. It is formulated with high levels of tackifier additive to resist dripping and throw-off. D-A BAR AND CHAIN OIL prevents rusting and reduces friction and heat build-up on cutting chain and guide bar. Anti-wear agents reduce metal-to-metal contact wear between the drive sprocket, the bar guide and the moving chain.

D-A Bar and Chain Oil is recommended for all makes of chain saws and all types of link chains that require lubrication - including motorcycles and bicycles as well as farm and industrial uses.

Product Features and Benefits

Extends bar, chain and sprocket life
Tackifier stays on the bar and chain
Easy pour
Resists "throw-off"
Quality oil and tackifier prevent moisture from oxidizing
bar and chain
Prevents rusting
Reduces friction and wear
Easy to use

PRODUCT AT A GLANCE

- Extends life of bar, chain and sprocket
- Tackifier stays where put
- Resists "throw-off"
- Resists rusting



D-A Lubricant Company, Inc.

801 Edwards Drive, Lebanon, IN 46052 • TEL: 317.923.5321 • FAX: 765.482.3065 • EMAIL: dalube@dalube.com
www.dalube.com





Bar and Chain Oil

Typical Applications

D-A BAR AND CHAIN OIL is recommended for all makes of chain saws and all types of link chains that require lubrication, including motorcycles, and bicycles, as well as farm and industrial uses.

Typical Properties

Viscosity @		
100 °C, cSt	ASTM D445	11.6
40 °C, cSt	ASTM D445	98.2
Viscosity Index	ASTM D2270	106
Flash Point °F	ASTM D92	466
°C	ASTM D92	241
Pour Point °F	ASTM D96	-40
°C	ASTM D96	-22
API Gravity, 60 °F	ASTM D287	28.8

Drum, 55 Gal 59102

To Order D-A Products, Call 1-800-OIL-LUBE (1-800-645-5823) or Fax orders to 765-482-3065

D-A Lubricant Company, Inc.

801 Edwards Drive, Lebanon, IN 46052 • TEL: 317.923.5321 • FAX: 765.482.3065

Email: dalube@dalube.com

