

Product Description

D-A Citrasense[™] is a general purpose degreaser designed for use in a broad range of industrial cleaning applications.

This product is formulated with a solvent derived from natural citrus sources. It is designed to be highly efficient for removal of all types of oily and greasy soils including grease, gear oils or corrosion preventatives. Apply Citrasense to soiled surfaces and agitate as necessary to remove stubborn soils. Rinse surface with water to remove soil.

Storage

Store away from heat, sparks and open flame. Store in tightly sealed containers. If storing product in container other than original shipping container, stainless steel tanks or fluorocarbon-barrier plastic containers are recommended.

Product Features and Benefits

Formulated specifically for use in cleaning industrial equipment including metals, nylon, stainless steel and certain plastics. Citrus-based formulation loosens oils, greases and other soil easily and washes off with water.

PRODUCT AT A GLANCE

- General Purpose Degreaser / Cleaner
- Solvent Derived from Natural Citrus Sources
- Highly Efficient



D-A Lubricant Company, Inc.

801 Edwards Drive, Lebanon, IN 46052 • TEL: 317.923.5321 • FAX: 765.482.3065 • EMAIL: dalube@dalube.com
www.dalube.com



Typical Applications

D-A Citrasense™ is suitable for use in cleaning a wide range of industrial applications:

COMPATIBILITY REFERENCE:

Aluminum	No effect/Excellent	Nylon	No effect/Excellent
Burma N	No effect/Excellent	Phenolic	No effect/Excellent
Carbon/Ceramic	No effect/Excellent	Polyethylene	Moderate effect/Fair
Carbon/Graphite	No effect/Excellent	Polypropylene	Moderate effect/Fair
Carpenter 20	No effect/Excellent	PVC	Minor effect/Good
Cast Bronze	No effect/Excellent	Ryton	Unknown
Ceramagnet A	No effect/Excellent	Silicone	Severe effect/Not recommended
Ceramic	No effect/Excellent	Stainless steel (304)	No effect/Excellent
CPV	No effect/Excellent	Stainless steel (316)	No effect/Excellent
Cycolac (ABS)	Minor effect/Good	Stainless steel (440)	No effect/Excellent
Delrin (Acetal)	Severe effect/Not recommended	Teflon	No effect/Excellent
EPDM	Unknown	Titanium	No effect/Excellent
Epoxy	No effect/Excellent	Tygon	Moderate effect/Fair
Hastelloy C	No effect/Excellent	Viton	No effect/Excellent
Hypalon	Unknown		
Kel-F	Unknown		
Kynar (PVDF)	No effect/Excellent		
Natural Rubber	Moderate effect/Fair		
Neoprene	Moderate effect/Fair		
Nitrile	No effect/Excellent		
Noryl	Unknown		

Recommended Gasket Material:

Man-holes use Viton
Pump parts use Teflon
O-Rings use Fluro-Silicon
Rubber gaskets must be periodically replaced.

Typical Properties

Appearance	Visual	Clear Liquid
Odor		Citrus
Density, pounds per gallon	ASTM D4052	7.1
Flash Point, °F	ASTM D92	115
°C		46
VOC%		94.5
	Drum, 55 gal	15002
	Qtr Drum, 16 gal	15006
	Pail, 5 Gal	15008

To Order D-A Products, Call 1-800-OIL-LUBE (1-800-645-5823) or Fax orders to 765-482-3065

D-A Lubricant Company, Inc.

801 Edwards Drive, Lebanon, IN 46052 • TEL: 317.923.5321 • FAX: 765.482.3065

Email: dalube@dalube.com • www.dalube.com

