

Product Description

D-A Heat Transfer Oil 22 may be used in all major asphalt heaters and other types of heat transfer systems requiring a highly stable oil as a medium for storing and transferring heat. It possesses excellent natural temperature stability when subjected to the temperatures encountered in most heater systems. It is not unusual for some heat transfer systems to operate at an oil temperature in excess of 400°F, which means that the heater tube walls themselves can be considerably hotter. The most important criteria of a heat transfer oil is temperature stability.

D-A Heat Transfer Oil 22 provides the required temperature stability with a minimum of coking, which is the reduction of a petroleum product to carbon in an atmosphere devoid of oxygen. D-A's research indicates that the tendency of an oil to coke is dependent on the methods used to refine the base oil.

D-A Heat Transfer Oil 22 is produced from a carefully selected base oil that has been refined in such a manner as to provide maximum natural temperature stability.

Product Features and Benefits

Supports the heating oil performance requirements established by the manufacturers of asphalt heaters, ideal for use in any heat application.

Contains extremely effective oxidation inhibitors for longer oil life and minimum coking.

Performance-proven temperature stability means the oil won't break down under severe heat stress.

Compounded with high quality stable base stocks fortified with additives designed to effectively retard the deposit of carbon (coking) on heater tubes, resulting in minimal tube fouling.



D-A Lubricant Company, Inc.



Typical Applications

- High temperature heat transfer systems
- Residual fuel heating systems
- Asphalt heaters
- Any system using mineral oil as a medium for storing and transferring heat

Typical Properties

ISO Viscosity		22
Viscosity @		
100°C, cSt	ASTM D445	4.35
40°C, cSt	ASTM D445	22
Viscosity Index	ASTM D2270	105
API Gravity	ASTM D287	31.6
Flash Point, °F	ASTM D92	374
°C	ASTM D92	190
Fire Point, °F	ASTM D92	21
°C	ASTM D92	-6
Maximum System Temperature		
Closed System, °F		550
°C		288
Open System, °F		340
°C		171

D-A Part No.	Drum, 55 gal	58042
	Pail, 5 gal	58048



To Order D-A Products, Call 1-800-OIL-LUBE (1-800-645-5823) or Fax orders to 765-482-3065

D-A Lubricant Company, Inc.

801 Edwards Drive, Lebanon, IN 46052 • TEL: 317.923.5321 • FAX: 765.482.3065 • EMAIL: dalube@dalube.com

www.dalube.com