

Product Description

D-A ProLith™ 3 is a multi-purpose extreme pressure grease for lubrication of heavy duty trucks, construction and mining equipment. D-A ProLith 3 is a lithium grease which has been scientifically formulated with moly additives for excellent performance under tough operating conditions. ProLith 3's extreme pressure additive system is non-corrosive to all types of bearing and gear metallurgy, even those having sensitive metallurgy such as bronze, brass and copper.

D-A ProLith 3 is available in two NLGI grades: 1 and 2, permitting the user to select the correct grease consistency to fit each application during all times of the year.

Product Features and Benefits

Special blend of extreme pressure additives limits wear and reduces friction in normal and severe machine service.

Formulated to meet most OEM guidelines for severe service in pin and bushing sets, bearings, general chassis lubrication and more.

Rust and corrosion preventatives protect both ferrous and non-ferrous metals in damp or corrosive environments.

Excellent shear stability and bleed resistance protect against grease leakage and helps control lubrication costs.

Pumps easily from tubes and other types of containers, perfect for use in central lubrication systems or in all weather conditions.

PRODUCT AT A GLANCE

- Lithium Grease
- Contains 3% Moly
- Multi-Purpose
- Extreme Pressure
- Excellent in tough operating conditions



D-A Lubricant Company, Inc.

801 Edwards Drive, Lebanon, IN 46052 • TEL: 317.923.5321 • FAX: 765.482.3065 • EMAIL: dalube@dalube.com
www.dalube.com



Supports the Performance Requirements of:

General Lubrication
Bearings

Chassis Lubrication
Bushings and Pins

Typical Properties

	ASTM D217	#1	#2
NLGI Grade	ASTM D217	Lithium	Lithium
Soap Type	ASTM D128	Gray	Gray
Color	Visual	310-340	265-295
Penetration, Worked 60@77 F	ASTM D217	360 (182)	360 (182)
Dropping Point, °F (°C)	ASTM D2265	5	3
Oil Separation, wt %	ASTM D6184	315	315
Four Ball EP, Weld Load kg	ASTM D2596	0.6	0.6
Four Ball Wear, Scar Dia., mm	ASTM D2266	Pass	Pass
Bearing Rust Test	ASTM D1743	50	50
Timken OK Load, lbs/ Min.	ASTM D2509	220	220
Base Oil Viscosity @ 40 °C	ASTM D445		

D-A Part Number:	Drum - 400 lb	12422	12432
	Quarter Drum - 120 lb	12426	12436
	Pail - 35 lb	12428	12438
	Cartridges - 43 lb	12427T	12437T

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture. The information contained herein is subject to change without notice.

To Order D-A Products, Call 1-800-OIL-LUBE (1-800-645-5823) or Fax orders to 765-482-3065

D-A Lubricant Company, Inc.

801 Edwards Drive, Lebanon, IN 46052 • TEL: 317.923.5321 • FAX: 765.482.3065

Email: dalube@dalube.com • www.dalube.com

