

Product Description

D-A evolve[™] tractor fluid is a proven premium grade transmission and hydraulic fluid providing superior performance for severe service off-highway applications. It is formulated from high-quality re-refined and virgin base stocks fortified with a high-performance additive system to extend component life and improve performance characteristics. D-A evolve[™] tractor fluid meets the specifications of most major agricultural equipment manufacturers, allowing users to stock one fluid to meet both transmission and hydraulic system needs.

Product Features and Benefits

Improves hydraulic pump and gear train life to help reduce maintenance costs.
Improved oxidation stability extends oil life.
Improved frictional properties prevent grabbing or chattering of wet brakes and PTO clutches.
Excellent water tolerance and low temperature fluidity provides protection in all working environments.
Provides rust and corrosion protection for all types of metal surfaces, increasing component life.
Complies with hydraulic and transmission field service requirements of major agricultural equipment manufacturers reducing the need to inventory separate lubricants.

PRODUCT AT A GLANCE

- Premium Grade Tractor Fluid
- Transmission and Hydraulic Fluid
- Designed for use in Severe Service
- Meets requirements of most major agricultural manufacturers
- Good for use in Cold Weather



D-A Lubricant Company, Inc.

801 Edwards Drive, Lebanon, IN 46052 • TEL: 317.923.5321 • FAX: 765.482.3065 • EMAIL: dalube@dalube.com
www.dalube.com



Typical Applications

John Deere — JDM JC20A & JC20C
 Ford New Holland — FNHA-2-C-201.00; ESN-M2C134 A, B, C & D; ESN-M2C86B
 Massey-Ferguson — M-1141; M-1135; M-1129-A; M-1127-A&B; M-1110
 Case — MS-1207; MS-1210/JIC-145; MS-1204/JIC-185; MS-1230
 Kubota — UDT
 White Farm — Q-1826 HTF
 Agco/Deutz-Allis — Power Fluid 821XL
 Allison — C-3 and C-4
 Volvo — WB101

Typical Properties

| | | |
|-----------------------------------|------------|--------|
| Kinematic Viscosity | | |
| @ 100°C, cSt | ASTM D445 | 9.5 |
| @ 40°C, cSt | ASTM D445 | 61.8 |
| Brookfield Viscosity | | |
| @ -18°C, cP | ASTM D5293 | 3,720 |
| @ -20°C, cP | ASTM D5293 | 4,500 |
| @ -29°C, cP | ASTM D4684 | 19,200 |
| @ -35°C, cP | ASTM D2983 | 57,000 |
| Viscosity Index | ASTM D2270 | 140 |
| Flash Point, | | |
| °F | ASTM D92 | 425 |
| °C | ASTM D92 | 218 |
| API Gravity | ASTM D287 | 28.0 |
| Humidity Cabinet Rust Test, Hours | | 200+ |
| Vickers Pump Test | | PASS |
| Tractor Performance Tests | | |
| Transmission Durability | | PASS |
| Gear Wear Protection | | PASS |
| Brake Chatter and Capacity | | PASS |
| Power Take Off Clutch | | PASS |
| | Bulk | 57551 |

To Order D-A Products, Call 1-800-OIL-LUBE (1-800-645-5823) or Fax orders to 765-482-3065

D-A Lubricant Company, Inc.

801 Edwards Drive, Lebanon, IN 46052 • TEL: 317.923.5321 • FAX: 765.482.3065

Email: dalube@dalube.com • www.dalube.com

