

Product Description

D-A PresurFlo[™] FR is a premium, water-glycol, fire resistant fluid formulated with diethylene glycol. It is designed to provide optimum performance in hydraulic systems where fire resistant fluids are required.

D-A PresurFlo FR contains an adequate amount of water to prevent ignition that could occur in hydraulic systems operating under high pressure through sudden line ruptures or fluid contact with a high temperature source. PresurFlo FR includes additives that provide lubricity, corrosion protection and the overall performance demanded by today's high-performance hydraulic systems. D-A PresurFlo FR contains no nitrites or nitrosamines.

D-A PresurFlo FR provides a high viscosity index, low pour point and excellent heat transfer and anti-foam performance. These properties along with the addition of an anti-wear component, provide extended pump life in systems operating under high pressure or overloaded conditions.

Product Features and Benefits

Fire resistant to increase job site safety.

Limits wear in high pressure vane pumps for longer pump life and reduced operating cost.

Provides wear control for steel, brass and bronze pump parts when operating at maximum pressure ratings, resulting in excellent pump protection and more cost efficient operation.

Specifically blended to prevent combustion if fluid should come in contact with a high temperature source.

PRODUCT AT A GLANCE

- Fire Resistant
- Hydraulic Fluid
- Blended to prevent combustion
- Provides wear control at maximum pressure ratings
- Contains NO Nitrites or Nitrosamines



D-A Lubricant Company, Inc.

801 Edwards Drive, Lebanon, IN 46052 • TEL: 317.923.5321 • FAX: 765.482.3065 • EMAIL: dalube@dalube.com

www.dalube.com



Typical Applications

For use in most types of hydraulic equipment found in steel mills, die-casting and transmission plants.

U.S. Steel Requirement #171
Factory Mutual Approved
USDA Classification H2

Typical Properties

ISO Viscosity Grade		46
Viscosity		
@ 100°C, cSt	ASTM D445	8.8
@ 40°C, cSt	ASTM D445	41.8
Flash Point,		
°F	ASTM D92	None
°C	ASTM D92	None
API Gravity @ 60 °F	ASTM D287	1.09
Pour Point		
°F	ASTM D97	-50
°C	ASTM D97	-46
Density, Lbs per Gal @ 60 °F	ASTM D4052	9.1
Brix Reading, AO Model 10431		44.5
Color	Visual	Red
Appearance	Visual	Clear and Bright
pH		9.4
Four Ball Wear Test, 40 kg load (mm)	ASTM D2266	0.7
Liquid and vapor Phase Corrosion of Steel		Nil
D-A Part No.	Drum, 55 Gal Pail, 5 Gal	55252

To Order D-A Products, Call 1-800-OIL-LUBE (1-800-645-5823) or Fax orders to 765-482-3065

D-A Lubricant Company, Inc.

801 Edwards Drive, Lebanon, IN 46052 • TEL: 317.923.5321 • FAX: 765.482.3065

Email: dalube@dalube.com • www.dalube.com

