

AutoTrans Super LV, AutoTrans Multi-Vehicle, AutoTrans Super Plus

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO < 3%)	(CAS-No.) 72623-87-1	80 – 90	Asp. Tox. 1, H304
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (DMSO <3%)	(CAS-No.) 72623-86-0	1 – 3	Asp. Tox. 1, H304
Thio alkyl long chain alkyl ester	(CAS-No.) trade secret	0.01 – 0.2	Eye Irrit. 2A, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after skin contact : May cause an allergic skin reaction.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

- Fire hazard : Burning produces irritating, toxic and noxious fumes.
- Reactivity : No dangerous reactions known.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear fire/flame resistant/retardant clothing. Wear recommended personal protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid all eye and skin contact and do not breathe vapour and mist. Use personal protective equipment as required.

6.1.1. For non-emergency personnel

- Protective equipment : Refer to section 8.2.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Refer to section 8.2.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

AutoTrans Super LV, AutoTrans Multi-Vehicle, AutoTrans Super Plus

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
- Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep only in the original container in a cool well ventilated place.
- Incompatible products : Strong bases. Strong acids. Strong oxidizers.
- Incompatible materials : Sources of ignition. Direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO < 3%) (72623-87-1)		
Not applicable		
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (DMSO <3%) (72623-86-0)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ (oil mist)
OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³ (oil mist)
Thio alkyl long chain alkyl ester (trade secret)		
Not applicable		

8.2. Appropriate engineering controls

- Appropriate engineering controls : Avoid creating mist or spray. Avoid splashing. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide local exhaust or general room ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear suitable gloves resistant to chemical penetration. nitrile rubber gloves. natural rubber gloves

Eye protection:

Chemical goggles or safety glasses

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Use an approved respirator equipped with oil/mist cartridges.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Colour : red

AutoTrans Super LV, AutoTrans Multi-Vehicle, AutoTrans Super Plus

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odour	: petroleum
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 190 °C
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 28 - 34 mm ² /s @ 40 °C
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO <3%) (72623-87-1)	
LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rabbit	> 2000 mg/kg bodyweight
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (DMSO <3%) (72623-86-0)	
LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rabbit	> 2000 mg/kg bw/day
Thio alkyl long chain alkyl ester (trade secret)	
LD50 oral rat	> 10000 mg/kg

AutoTrans Super LV, AutoTrans Multi-Vehicle, AutoTrans Super Plus

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: 28 - 34 mm ² /s @ 40 °C
Likely routes of exposure	: Inhalation. Skin and eye contact.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.

SECTION 12: Ecological information

12.1. Toxicity

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO < 3%) (72623-87-1)	
LC50 fish 1	> 100 mg/l
EC50 Daphnia 1	> 10000 mg/l
ErC50 (algae)	>= 100 mg/l
NOEC (acute)	> 100 mg/kg

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based (DMSO < 3%) (72623-86-0)	
LC50 fish 1	> 100 mg/l
EC50 Daphnia 1	> 10000 mg/l
NOEC (acute)	> 1000 mg/l

Thio alkyl long chain alkyl ester (trade secret)	
LC50 fish 1	> 1000 mg/l 96 h
EC50 Daphnia 1	9.5 mg/l 48 h

12.2. Persistence and degradability

AutoTrans Super LV, AutoTrans Multi-Vehicle, AutoTrans Super Plus	
Persistence and degradability	Not established.

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO < 3%) (72623-87-1)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	2 - 4 %

Thio alkyl long chain alkyl ester (trade secret)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	11 - 14 %

12.3. Bioaccumulative potential

AutoTrans Super LV, AutoTrans Multi-Vehicle, AutoTrans Super Plus	
Bioaccumulative potential	Not established.

Thio alkyl long chain alkyl ester (trade secret)	
Bioconcentration factor (BCF REACH)	140 - 410
Bioaccumulative potential	Does not bioaccumulate significantly.

12.4. Mobility in soil

Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based (DMSO < 3%) (72623-87-1)	
Mobility in soil	22 %

AutoTrans Super LV, AutoTrans Multi-Vehicle, AutoTrans Super Plus

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated.

Transport by sea

Transport document description (IMDG) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (alkyl phosphites), 9, III, MARINE POLLUTANT
UN-No. (IMDG) : 3082
Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Class (IMDG) : 9 - Miscellaneous dangerous substances and articles
Packing group (IMDG) : III - substances presenting low danger
Limited quantities (IMDG) : 5 L

Air transport

Transport document description (IATA) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (alkyl phosphites), 9, III
UN-No. (IATA) : 3082
Proper Shipping Name (IATA) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Class (IATA) : 9 - Miscellaneous Dangerous Goods
Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

No additional information available

Thio alkyl long chain alkyl ester (trade secret)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

No additional information available

Thio alkyl long chain alkyl ester (trade secret)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

AutoTrans Super LV, AutoTrans Multi-Vehicle, AutoTrans Super Plus

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Thio alkyl long chain alkyl ester (trade secret)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
 Listed on KECI (Korean Existing Chemicals Inventory)
 Listed on NZIoC (New Zealand Inventory of Chemicals)
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
 Listed on Taiwan National Chemical Inventory
 Listed on the AICS (Australian Inventory of Chemical Substances)
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

15.3. US State regulations

⚠ WARNING: This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Sulphur dioxide(7446-09-5)		X				10000 µg/day
Benzene(71-43-2)	X	X	X		6.4 µg/day (oral); 13 µg/day (inhalation)	24 µg/day (oral); 49 µg/day (inhalation)

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Data sources : European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.

Other information : None.

Full text of H-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Skin Sens. 1	Skin sensitisation, Category 1
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:


	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	STEL: Short Term Exposure Limits
	TSCA: Toxic Substances Control Act
	TWA: Time Weighted Average
	WEL: Workplace Exposure Limit

AutoTrans Super LV, AutoTrans Multi-Vehicle, AutoTrans Super Plus

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard	: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard	: 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



SDS prepared by The Redstone Group
6077 Frantz Rd.
Suite 206
Dublin, OH USA 43017
+1.614.923.7472
www.redstonegrp.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product