

# Bar and Chain Oil



## Product Description

All Season D-A **Bar and Chain Oil** is formulated to insure good performance on all link chain and chain bars including chain saw bars. Premium quality D-A **Bar and Chain Oil** extends the life of the bar, chain and sprocket by protecting against wear. It is formulated with high levels of tackifier additive to resist dripping and throw-off. D-A **Bar and Chain Oil** prevents rusting and reduces friction and heat build-up on cutting chain and guide bar. Anti-wear agents reduce metal-to-metal contact wear between the drive sprocket, the bar guide and the moving chain.

D-A **Bar and Chain Oil** is recommended for all makes of chain saws and all types of link chains that require lubrication - including motorcycles and bicycles as well as farm and industrial uses.

## Product Features and Benefits

- Extends bar, chain and sprocket life
- Tackifier stays on the bar and chain
- Easy pour
- Resists "throw-off"
- Quality oil and tackifier prevent moisture from oxidizing bar and chain
- Prevents rusting
- Reduces friction and wear
- Easy to use

## Typical Applications

D-A **Bar and Chain Oil** is recommended for all makes of chain saws and all types of link chains that require lubrication, including motorcycles, and bicycles, as well as farm and industrial uses.

## Typical Properties

<b>Bar and Chain Oil</b>	Test Method	100	150	220
Viscosity @ 100 °C, cSt	ASTM D445	12.0	15.7	19.9
@ 40 °C, cSt	ASTM D445	97.7	148.4	217.4
Viscosity Index	ASTM D2270	114	109	105
Pour Point, °F (°C)	ASTM D97	-29 (-34)	-17 (-27)	-9 (-23)
Flash Point °F (°C)	ASTM D92	445 (229)	455 (235)	460 (238)
API Gravity	ASTM D4052	30.6	29.6	28.7

### D-A Part Number:

Bulk	59101	59111	59121
Tote – 330 Gal	59103	59113	59123
Drum – 55 Gal	59102	N/A	N/A
Case – 4/1 Gal	59105	N/A	N/A