

Product Description

D-A **Calguard**™ is an uninhibited (contains no additives), anhydrous calcium soap product. Anhydrous calcium greases will afford better heat resistance than hydrated calcium greases. The D-A **Calguard**™ offers a dropping point of around 300°F (145°C). In addition to the temperature benefits, the D-A **Calguard**™ anhydrous calcium grease offers all the advantages of traditional calcium greases, including excellent adhesion, low temperature lubricity and water resistance. D-A **Calguard**™ is a uniquely tailored grease for industrial assembly where lubricity is critical, but not subjected to applied loads or corrosive environments. Anhydrous Calcium thickened greases like D-A **Calguard**™ offer good thermal stability and load carrying capability, very good shear stability and excellent water resistance.

Typical Applications

Marine	Construction
Agriculture	Forestry
Over-the-Road Truck Differentials	

Typical Properties

NLGI Grade	ASTM D217	2.5
Thickener Type	ASTM D128	Anhydrous Calcium
Color	Visual	Amber
Texture	Visual	Smooth
Worked Penetration	ASTM D217	255-280
Base Oil Viscosity @ 40°C	ASTM D445	150
Dropping Point, °F (°C)	ASTM D2265	300 (145) min

D-A Part Number:

Bulk

12171