

Circulating Oil GR II™



Product Description

D-A **Circulating Oil GR II™** is a premium quality circulating oil available in ISO viscosity grade 460. It is designed to be environmentally friendly. D-A **Circulating Oil GR II™** is zinc and phenol free. The highest quality petroleum base oil is selected for its natural stability and for its compatibility with high performance components. Exceptional rust and oxidation resistance are results of the unique formulation of select base oil and additives. Anti-wear performance is achieved by the basic formulation which is of a non-corrosive nature.

D-A **Circulating Oil GR II™** supports the performance requirements of lubricants used in *Morgoil® Bearings. These high quality oils meet Morgoil® Advanced Lubricant (Super Demulsibility) specification (Rev. 2.4 dated Feb. 29, 2007). *Morgoil® is a registered trademark of Morgan Co.

Product Features and Benefits

- Resistance to oxidation and the formation of deposits.
- Fast separation from water protects bearings from water damage.
- Protection against rust and corrosion provides longer bearing life.
- Compatibility with seal material provides excellent seal life.
- Environmentally favorable (no zinc, phenol) - allows for use in environmentally sensitive areas.

Typical Applications

D-A **Circulating Oil GR II™** supports the performance requirements of lubricants used in Morgoil® Bearings. These high quality oils meet Morgoil® Advanced Lubricant (Super Demulsibility) specification (Rev. 2.4 dated Feb. 29, 2007). Use generally in any lubricating oil circulation system that is well-engineered and protected from leakage or contamination which would require frequent oil replacement. Designed for lubrication of bearings, gears and ways. *Morgoil® is a registered trademark of Morgan Co.

Typical Properties

ISO Viscosity Grade	Test Method	460
Viscosity @ 100°C, cSt	ASTM D445	34.2
@ 40°C, cSt	ASTM D445	460
Viscosity Index	ASTM D2270	110
Pour Point, °F (°C)	ASTM D97	10 (-12)
Flash Point, COC, °F (°C)	ASTM D92	558 (292)
API Gravity	ASTM D4052	27.5
Copper Strip Corrosion	ASTM D130	1a
Rust Test	ASTM D665	Pass
Foam Test	ASTM D892	Pass

D-A Part Number:

Bulk

57281

Tote – 330 Gal

57283