

SECTION 1: Identification

1.1. Identification

Product name : GearTec SAE 80W-90, GearTec SAE 85W-140, GearTec SAE 90

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Lubricant

Restrictions on use : No additional information available

1.3. Supplier

D-A Lubricant Company, Inc.
801 Edwards Dr
Lebanon, IN 46052
T 317-923-5321, Toll Free 1-800-873-2582
www.dalube.com

1.4. Emergency telephone number

Emergency number : 1-800-899-9004 Toll-Free USA/CAN 24 hours

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS classification

Not classified

2.2. GHS Label elements, including precautionary statements

GHS labelling

No labelling applicable

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS_US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS classification
Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%)	(CAS-No.) 64742-54-7	0 - 50	Asp. Tox. 1, H304
Long-chain alkyl amine (HMIRA Reg. No. 9939; Filing date 4/11/2016)	(CAS-No.) trade secret	0.1 - 0.9	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 2 (Inhalation:gas), H330 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Give oxygen or artificial respiration if necessary.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. Wash skin thoroughly with mild soap and water. If skin irritation or rash

GearTec SAE 80W-90, GearTec SAE 85W-140, GearTec SAE 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after skin contact : Prolonged or repeated contact may cause skin to become dry or cracked.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

- Fire hazard : Burning produces irritating, toxic and noxious fumes.
- Reactivity : No dangerous reactions known.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear fire/flame resistant/retardant clothing. Wear recommended personal protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid all eye and skin contact and do not breathe vapour and mist. Use personal protective equipment as required.

6.1.1. For non-emergency personnel

- Protective equipment : Refer to section 8.2.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Refer to section 8.2.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. On land, sweep or shovel into suitable containers. Collect spillage. Minimise generation of dust. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
- Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep only in the original container in a cool well ventilated place.

GearTec SAE 80W-90, GearTec SAE 85W-140, GearTec SAE 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Incompatible products : Strong bases. Strong acids. Strong oxidizers.
Incompatible materials : Sources of ignition. Direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
ACGIH	ACGIH STEL (mg/m ³)	10 mg/m ³
OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³
Long-chain alkyl amine (HMIRA Reg. No. 9939; Filing date 4/11/2016) (trade secret)		
Not applicable		

8.2. Appropriate engineering controls

Appropriate engineering controls : Avoid creating mist or spray. Avoid splashing. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide local exhaust or general room ventilation.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear suitable gloves resistant to chemical penetration. nitrile rubber gloves. natural rubber gloves

Eye protection:

Chemical goggles or safety glasses

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Use an approved respirator equipped with oil/mist cartridges.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Colour : red
Odour : petroleum
Odour threshold : No data available
pH : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : No data available
Flash point : > 222 °C
Relative evaporation rate (butylacetate=1) : No data available
Flammability (solid, gas) : Non flammable.
Vapour pressure : No data available
Relative vapour density at 20 °C : No data available
Relative density : No data available
Solubility : No data available
Log Pow : No data available
Auto-ignition temperature : No data available

GearTec SAE 80W-90, GearTec SAE 85W-140, GearTec SAE 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Decomposition temperature	: No data available
Viscosity, kinematic	: 140 - 415 mm ² /s @ 40°C
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.53 mg/l/4h

Long-chain alkyl amine (HMIRA Reg. No. 9939; Filing date 4/11/2016) (trade secret)

LD50 oral rat	612 mg/kg
LD50 dermal rat	251 mg/kg
LC50 inhalation rat (ppm)	157 ppm/4h
ATE (oral)	612 mg/kg bodyweight
ATE (dermal)	251 mg/kg bodyweight
ATE (gases)	157 ppmv/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitisation	: Not classified. (Long-chain alkyl amine not sensitizing <1.5%)
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: 140 - 415 mm ² /s @ 40°C

GearTec SAE 80W-90, GearTec SAE 85W-140, GearTec SAE 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Likely routes of exposure : Inhalation. Skin and eye contact.
Symptoms/effects after skin contact : Prolonged or repeated contact may cause skin to become dry or cracked.

SECTION 12: Ecological information

12.1. Toxicity

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

EC50 crustacea > 10000 mg/l

12.2. Persistence and degradability

GearTec SAE 80W-90, GearTec SAE 85W-140, GearTec SAE 90

Persistence and degradability Not established.

12.3. Bioaccumulative potential

GearTec SAE 80W-90, GearTec SAE 85W-140, GearTec SAE 90

Bioaccumulative potential Not established.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated.

Transport by sea

Not regulated.

Air transport

Not regulated.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

15.2. International regulations

CANADA

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Long-chain alkyl amine (HMIRA Reg. No. 9939; Filing date 4/11/2016) (trade secret)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

GearTec SAE 80W-90, GearTec SAE 85W-140, GearTec SAE 90

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Long-chain alkyl amine (HMIRA Reg. No. 9939; Filing date 4/11/2016) (trade secret)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Distillates (petroleum), hydrotreated heavy paraffinic (DMSO < 3%) (64742-54-7)
Listed on the AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on KECI (Korean Existing Chemicals Inventory) Listed on the TCSI (Taiwan Chemical Substance Inventory) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on NZIoC (New Zealand Inventory of Chemicals)
Long-chain alkyl amine (HMIRA Reg. No. 9939; Filing date 4/11/2016) (trade secret)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on KECI (Korean Existing Chemicals Inventory) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on Taiwan National Chemical Inventory Listed on the AICS (Australian Inventory of Chemical Substances) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

15.3. US State regulations

⚠ WARNING: This product can expose you to Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	Carcinogenicity	Developmental toxicity	Reproductive toxicity male	Reproductive toxicity female	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Ethylene oxide(75-21-8)	X	X	X	X	2 µg/day	20 µg/day
Propylene oxide(75-56-9)	X					
1,4-dioxane(123-91-1)	X				30 µg/day	
Ethyl acrylate(140-88-5)	X				not determined	

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 09/20/2019
 Data sources : European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.
 Other information : None.

Full text of H-statements:

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.

GearTec SAE 80W-90, GearTec SAE 85W-140, GearTec SAE 90

Safety Data Sheet


according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	LD50: Lethal Dose for 50% of the test population
	STEL: Short Term Exposure Limits
	TSCA: Toxic Substances Control Act
	TWA: Time Weighted Average
	WEL: Workplace Exposure Limit

NFPA health hazard	: 1 - Materials that, under emergency conditions, can cause significant irritation.
NFPA fire hazard	: 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Indication of changes:

Composition/information on ingredients. Classification.

SDS prepared by The Redstone Group
6077 Frantz Rd.
Suite 206
Dublin, OH USA 43017
+1.614.923.7472
www.redstonegrp.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.