

# HydraTrans 155 EX™



## Product Description

D-A **HydraTrans 155 EX™** is a proven premium grade, high viscosity transmission and hydraulic fluid providing superior performance for severe service off-highway and agriculture applications. It is formulated from high-quality base stocks fortified with a high-performance additive system to extend component life and improve performance characteristics. D-A **HydraTrans 155 EX™** supports the performance requirements for most major construction and agricultural equipment manufacturers, allowing users to stock one fluid to meet both transmission and hydraulic system needs.

## Product Features and Benefits

Improves hydraulic pump and gear train life to help reduce maintenance costs.

Improved oxidation stability extends oil life.

Improved frictional properties prevent grabbing or chattering of wet brakes and PTO clutches.

Excellent water tolerance and low temperature fluidity provides protection in all working environments.

Provides rust and corrosion protection for all types of metal surfaces, increasing component life.

Supports the performance requirements of both hydraulic and transmission field service for major construction and agricultural equipment manufacturers reducing the need to inventory separate lubricants.

## Typical Applications

AGCO	Denison HF-0, HF-1, HF-2	White Farm/MM/Oliver/New Idea
AGCO Power Fluid 821XL®	Hesston-Fiat Multi-F, Multi-G	Q-1705
Allis Power Fluid 821®	JCB	Q-1722, 1766, 1766B
Deutz-Allis 272843, 257541, 246634	John Deere	Q-1802
Massey Ferguson M1135, M1141, M1143, M1145	JDM J14B, J14C	Q-1826
Massey Ferguson M1110, M1127A/B, M1129A	JDM J20A, J20B	Type 55
Allison C-3, C-4	JDM J20C, J20D	ZF
API GL-4	JDM J21A	TE-ML 03E, TE-ML 03F
CNH	Komatsu and Komatsu Dresser	TE-ML 05E, TE-ML 05F
ESN-M2C134-A, B, C, D	B-06-001, B-06-002	TE-ML 06K
ESN-M2C41-B	Kubota UDT	
ESN-M2C43	Leyland	
ESN-M2C86B, C	Link Belt	
MAT 3505/MS-1209 (Ultra)	Sauer Sundstrand	
MAT 3525/FNHA-2C-201	Sperry-Vickers I-286-S, M-2950-S	
MAT 3526/FNHA-2C-200A	Sundstrand Hydraulics (Plessey)	
JIC 143/144, 145, 185	Vickers 35VQ25, M-2952-S	
MS-1204, 1206, 1207, 1209, 1210	Volvo WB101	

## Typical Properties

HydraTrans 155 EX™	Test Method	
Viscosity		
@ 100°C, cSt	ASTM D445	9.96
@ 40°C, cSt	ASTM D445	51.18
Viscosity Index	ASTM D2270	186
Pour Point, °F (°C)	ASTM D97	-45 (-43)
Flash Point, °F (°C)	ASTM D92	424 (218)
API Gravity	ASTM D4052	31.8

### D-A Part Number:

Bulk	57561
Tote – 330 Gal	57563