

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Reliant HD™ Multi-Vehicle (Yellow) 50/50 AFC, Reliant HD™ Multi-Vehicle Antifreeze/Coolant - Concentrate

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Antifreeze.
Coolant.

1.3. Details of the supplier of the safety data sheet

D-A Lubricant Company, Inc.
801 Edwards Dr
Lebanon, IN 46052
T 317-923-5321, Toll Free 1-800-873-2582
www.dalube.com

1.4. Emergency telephone number

Emergency number : 1-800-899-9004 Toll-Free USA/CAN 24 hours

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Acute toxicity (oral) Category 4 H302
Specific target organ toxicity (repeated exposure) Category 2 H373
Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS07

GHS08

Signal word (GHS-US) : Warning
Hazard statements (GHS-US) : H302 - Harmful if swallowed
H373 - May cause damage to organs through prolonged or repeated exposure
Precautionary statements (GHS-US) : P260 - Do not breathe mist, spray, vapors.
P264 - Wash hands thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product
P301+P312 - If swallowed: Call a doctor if you feel unwell
P314 - Get medical advice/attention if you feel unwell.
P330 - Rinse mouth.
P501 - Dispose of contents/container to Collection point

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

0.65% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
0.65% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
0.65% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Reliant HD™ Multi-Vehicle (Yellow) 50/50 AFC, Reliant HD™ Multi-Vehicle Antifreeze/Coolant - Concentrate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
Ethylene glycol	(CAS-No.) 107-21-1	50 - < 100	Acute Tox. 4 (Oral), H302 STOT RE 2, H373

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
- First-aid measures after skin contact : Take off immediately all contaminated clothing and wash it before reuse. Wash with plenty of soap and water.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- First-aid measures after ingestion : Rinse mouth. Call a POISON CENTER or doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : Causes damage to organs through prolonged or repeated exposure.
- Symptoms/effects after eye contact : Direct contact with the eyes is likely to be irritating.
- Symptoms/effects after ingestion : Swallowing a small quantity of this material will result in serious health hazard. Harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

All treatments should be based on observed signs and symptoms of distress in the patient.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Dry powder. Foam. Sand. Water spray.
- Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : No specific fire or explosion hazard.
- Reactivity : No dangerous reactions known.

5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter drains or water courses.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear fire/flame resistant/retardant clothing. Wear a self contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid all eye and skin contact and do not breathe vapor and mist.

6.1.1. For non-emergency personnel

- Protective equipment : Wear suitable gloves resistant to chemical penetration.
- Emergency procedures : Ventilate area.

6.1.2. For emergency responders

- Protective equipment : Wear suitable gloves. Where excessive vapor, mist, or dust may result, use approved respiratory protection equipment.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Absorb and/or contain spill with inert material, then place in suitable container.

Reliant HD™ Multi-Vehicle (Yellow) 50/50 AFC, Reliant HD™ Multi-Vehicle Antifreeze/Coolant - Concentrate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Take up in non-combustible absorbent material and shove into container for disposal.

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid breathing mist, spray, vapors.
Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use. Keep only in the original container in a cool well ventilated place.
Incompatible products : Strong oxidizing agents. Strong acids. Strong bases.
Incompatible materials : Heat sources. Direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethylene glycol (107-21-1)		
ACGIH	ACGIH Ceiling (mg/m ³)	100 mg/m ³
ACGIH	ACGIH Ceiling (ppm)	39.4 ppm
ACGIH	Remark (ACGIH)	Kidney dam; URT & eye irr
NIOSH	NIOSH REL (ceiling) (ppm)	50 ppm

8.2. Exposure controls

Appropriate engineering controls : Avoid creating mist or spray. Avoid splashing. Either local exhaust or general room ventilation is usually required.
Personal protective equipment : Avoid all unnecessary exposure.
Hand protection : It is a good industrial hygiene practice to minimize skin contact. In case of repeated or prolonged contact wear gloves.
Eye protection : In case of splashing or aerosol production: protective goggles.
Respiratory protection : In case of inadequate ventilation wear respiratory protection. Use an approved respirator equipped with oil/mist cartridges.
Other information : Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Yellow
Odor : odorless
Odor threshold : No data available
pH : 8 - 8.8
Melting point : No data available
Freezing point : -38 °C
Boiling point : > 107 °C
Flash point : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : No data available
Explosive limits : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Vapor pressure : < 0.1 mm Hg @ 20 °C

Reliant HD™ Multi-Vehicle (Yellow) 50/50 AFC, Reliant HD™ Multi-Vehicle Antifreeze/Coolant - Concentrate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative density	: 1.077 @ 20 °C
Relative vapor density at 20 °C	: > 1
Solubility	: Soluble in water.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Avoid excessive heat or cold. Keep away from sources of ignition.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Skin and eye contact; Inhalation

Acute toxicity : Oral: Harmful if swallowed.

Reliant HD™ Multi-Vehicle (Yellow) 50/50 AFC, Reliant HD™ Multi-Vehicle Antifreeze/Coolant - Concentrate	
ATE US (oral)	510.936 mg/kg body weight

Ethylene glycol (107-21-1)	
LD50 dermal rat	> 3500 mg/kg (mouse)
LC50 inhalation rat (mg/l)	> 2.5 mg/l/4h
ATE US (oral)	500 mg/kg body weight

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Ethylene glycol (107-21-1)	
LOAEL (oral,rat,90 days)	1000 mg/kg bodyweight/day
NOAEL (oral,rat,90 days)	150 mg/kg bodyweight/day kidney

Aspiration hazard : Not classified

Reliant HD™ Multi-Vehicle (Yellow) 50/50 AFC, Reliant HD™ Multi-Vehicle Antifreeze/Coolant - Concentrate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after eye contact	: Direct contact with the eyes is likely to be irritating.
Symptoms/effects after ingestion	: Swallowing a small quantity of this material will result in serious health hazard. Harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

Ethylene glycol (107-21-1)	
LC50 fish 1	72860 mg/l Pimephales promelas
EC50 Daphnia 1	> 100 mg/l
NOEC chronic fish	15380 mg/l Pimephales promelas
NOEC chronic crustacea	8590 mg/l Ceriodaphnia sp.

12.2. Persistence and degradability

Ethylene glycol (107-21-1)	
Persistence and degradability	Readily biodegradable.
Biodegradation	> 60 % 28 d

12.3. Bioaccumulative potential

Ethylene glycol (107-21-1)	
Log Pow	- 1.36
Bioaccumulative potential	Not expected to bioaccumulate.

12.4. Mobility in soil

12.5. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description	: RQ, UN3082 Environmentally hazardous substances, liquid, n.o.s. (Ethylene Glycol 10,309 lbs), 9, III
UN-No.(DOT)	: UN3082
Proper Shipping Name (DOT)	: Environmentally hazardous substances, liquid, n.o.s. Ethylene Glycol 10,309 lbs
Transport hazard class(es) (DOT)	: 9 - Class 9 - Miscellaneous hazardous material 49 CFR 173.140
Packing group (DOT)	: III - Minor Danger
Hazard labels (DOT)	: 9 - Class 9 (Miscellaneous dangerous materials)



Other information	: RQ: Conc. >= 5191 lbs, 50/50 >= 9819 lbs
-------------------	--

Transport by sea

Not applicable

Air transport

Not applicable

Reliant HD™ Multi-Vehicle (Yellow) 50/50 AFC, Reliant HD™ Multi-Vehicle Antifreeze/Coolant - Concentrate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Ethylene glycol	CAS-No. 107-21-1	50 - < 100%
-----------------	------------------	-------------

Ethylene glycol (107-21-1)	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
CERCLA RQ	5000 lb

15.2. International regulations

CANADA

Ethylene glycol (107-21-1)	
Listed on the Canadian DSL (Domestic Substances List)	
Non-Haz Substance, Unknown Acute Tox.	
Listed on the Canadian DSL (Domestic Substances List)	

EU-Regulations

Ethylene glycol (107-21-1)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	
Non-Haz Substance, Unknown Acute Tox.	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

National regulations

Ethylene glycol (107-21-1)	
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory	
Listed on the AICS (Australian Inventory of Chemical Substances)	
Listed on Taiwan National Chemical Inventory	
Listed on NZIoC (New Zealand Inventory of Chemicals)	
Listed on KECI (Korean Existing Chemicals Inventory)	
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)	
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)	

15.3. US State regulations

⚠ WARNING This product can expose you to Ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ethylene glycol (107-21-1)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
No	Yes	No	No		

Ethylene glycol (107-21-1)	
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities	
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances	
U.S. - Pennsylvania - RTK (Right to Know) List	

Reliant HD™ Multi-Vehicle (Yellow) 50/50 AFC, Reliant HD™ Multi-Vehicle Antifreeze/Coolant - Concentrate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 16: Other information

- Data sources : ESIS (European chemical Substances Information System; accessed at: <http://esis.jrc.ec.europa.eu/index.php?PGM=cla>. European Chemicals Agency (ECHA) Registered Substances list. Accessed at <http://echa.europa.eu/>. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. OSHA 29CFR 1910.1200 Hazard Communication Standard. TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>. United Nations Economic Commission for Europe: About the GHS. Accessed at http://www.unece.org/trans/danger/publi/ghs/ghs_welcome_e.html.
- Other information : None.


Full text of H-phrases:

H302	Harmful if swallowed
H373	May cause damage to organs through prolonged or repeated exposure

Abbreviations and acronyms:

	ACGIH (American Conference of Government Industrial Hygienists)
	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	LD50: Lethal Dose for 50% of the test population
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals)
	OSHA: Occupational Safety & Health Administration
	TSCA: Toxic Substances Control Act
	STEL: Short Term Exposure Limits
	TWA: Time Weighted Average

- NFPA health hazard : 0 - Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials.
- NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.
- NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



SDS prepared by: The Redstone Group, LLC.
6077 Frantz Rd
Suite 206
Dublin, Ohio USA 43016
614.923.7472
www.redstonegrp.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product