

Reliant Premium Plus™



Product Description

Reliant Premium Plus™ synthetic blend diesel engine oil is a lower viscosity next generation diesel engine oil formulated to meet the latest oil and engine technology standards. It has been created with the highest quality base stocks and latest advancements in additive technology for maximizing engine durability, service efficiency and fuel economy without sacrificing engine protection. **Reliant Premium Plus™** diesel engine oil is intended for modern (2017 and newer) diesel engines.

Reliant Premium Plus™ diesel engine oil has been formulated to exceed industry requirements of the new API FA-4 specification and tailored to meet leading OEM (Original Equipment Manufacturer) engine design / requirements for modern diesel engine service / operation. **Reliant Premium Plus™** diesel engine oil FA-4 may be incompatible with older API Commercial Category (API CK-4, CJ-4, CI-4 Plus, CI-4) oils and that any interchange (co-mingling) should be avoided, as earlier diesel engines may not be designed to operate with lower viscosity grades. Consult OEM prior to selection.

Product Features and Benefits

- Exceeds the new industry requirement of API FA-4
- State-of-art synthetic blend additive technology
- Maximum engine durability and fuel economy
- Optimum selection for mixed (new / older equipment) fleets
- Exceptional oxidation resistance, shear stability and aeration control
- Enhanced thermal stability
- Superior emission system(s) protection
- Millions of miles of extensive 'real world' field tests
- Premium wear protection
- 100% Made in the USA

Typical Applications

Reliant Premium Plus™ diesel engine oil is recommended for use in heavy duty diesel on-road applications specifying a FA-4 rated engine lubricant. Always consult your owner's manual for proper oil viscosity and quality selection.

Approvals and Specifications

Reliant Premium Plus™ 10W-30

API Approvals

API FA-4

OEM Approvals

DDC DFS 93K223

Meets the Performance Requirements of:

Cummins CES 20087

Typical Properties

SAE Viscosity Grade	J300	10W-30
Viscosity @ 100°C, cSt	ASTM D445	10.0
@ 40°C, cSt	ASTM D445	65.1
Viscosity Index	ASTM D2270	137
HTHS Viscosity, cP @150 °C	ASTM D4683	3.1
Pour Point, °F (°C)	ASTM D97	-36 (-33)
Flash Point, °F (°C)	ASTM D92	446 (230)
Sulfated Ash, Weight %	ASTM D874	1.0
TBN	ASTM D2896	10.8
CCS @ -25 °C, cP	ASTM D5293	5,690

D-A Part Number:

Bulk	52331
Tote – 330 Gal	52333
Drum – 55 Gal	52332