WearGuard™

Performance Engineered Lubricants

SYN 8000s Series

Product Description

WearGuard™ SYN 8000s Series are a fully synthetic, high performance gear oils formulated with superior polyalkylene glycol (PAG)-based oils. This product is blended with D-A's advanced **ChemGuard™** additive technology that includes premium anti-oxidants, anti-wear, and corrosion inhibitor additives.

The **WearGuard™ SYN 8000s Series** is recommended for industrial worm gear lubrication. They can also function well with Rotary Screw, Rotary Vane, Centrifugal and Reciprocating Compressors, including Vacuum Pumps and Enclosed gears and bearings.

Product Features and Benefits

- Resists hydrocarbon washout/dilution
- Soluble in water
- High load carrying capacity
- Reduced sludge and deposit formation
- Excellent oxidative and thermal stability
- Low friction and less power consumption
- Good steel on steel and steel on bronze anti-wear

D-A Lubricant Company, Inc.
801 Edwards Drive
Lebanon, IN 46052

dalube.com

Phone: 800.645.5823
Fax: 765.482.3065
Email: dalube@dalube.com

Typical Properties

ISO Viscosity Grade	Test Method	220
Viscosity @ 100°C, cSt @ 40°C, cSt	 ASTM D445 ASTM D445	 38 220
Viscosity Index	ASTM D2270	225
Pour Point, °F (°C)	ASTM D97	-35 (-37)
Flash Point, °F (°C)	ASTM D92	540 (280)
API Gravity	ASTM D4052	3.26
FZG Test, Pass Stage	ASTM D5182	12
Rust Test	ASTM D665	Pass

D-A Part Number:

Pail (Plastic) – 5 Gal IP73468