

# WearGuard™

*Performance Engineered Lubricants*



## D-A SYN HVI Compressor Oil 32/46

### Product Description

**WearGuard™ D-A SYN HVI Compressor Oil 32/46** is made from a severely hydro-treated, hydro-cracked hydrocarbon base fluid and designed especially for portable compressor applications. **WearGuard™ D-A SYN HVI Compressor Oil 32/46** has been formulated with excellent anti-wear and high film strength properties to provide the superior lubricating performance required for the severe service conditions in the portable compressor industry.

This lubricant is designed to extend portable compressor life well beyond the standard motor oils and hydraulic fluids typically used in this service.

### Product Features and Benefits

- Superior lubricating film strength
- Compatible with all seal materials
- Excellent rust & oxidation protection
- Superior wear protection
- Excellent low temperature performance
- Reduced foaming & fluid loss in severe service conditions
- Cleaner running operation, more resistant to varnish

## Typical Applications

Rotary Screw Compressors

## Typical Properties

ISO Viscosity Grade	Test Method	32/46
Viscosity @ 100°C, cSt	ASTM D445	7.82
@ 40°C, cSt	ASTM D445	38
Viscosity Index	ASTM D2270	183
Pour Point, °F (°C)	ASTM D97	-47 (-44)
Flash Point, °F (°C)	ASTM D92	439 (226)
API Gravity	ASTM D4052	34.9

### D-A Part Number:

Pail (Plastic) – 5 Gal

IP74318